

<u>Standard Features</u>	<u>Model</u>	<u>Sourcewell Price</u>
Chassis	GS-1930 half height swing gate, E-drive	\$17,227.01
Automatic leveling hydraulic outriggers (GS™-3232 only)	GS-1932 half height swing gate, E-drive	\$16,867.14
Descent, tilt and motion alarm	GS-2632 half height swing gate, E-drive	\$24,593.59
Dual LED flashing beacons	GS-3232 half height swing gate, E-drive	\$36,120.56
Dual wheel multi-disc brakes	GS-2646 full height swing gate, E-drive	\$24,519.39
Manual brake release	GS-3246 full height swing gate, E-drive	\$29,828.40
Electric brake release (E-drive only)	GS-4046 full height swing gate, E-drive	\$39,967.83
On-board diagnostic system with battery charge indicator	GS-4655 full height swing gate, E-drive	\$51,791.60
Pothole protection	Transport/Destination (each) - 1930, 1932	\$1,020
Proportional drive	Transport/Destination (each) - 2032, 2632, 2046, 2646	\$1,350
Rear recessed charger receptacle	Transport/Destination (each) - 3232, 3246	\$1,450
Side & rear forklift pockets (GS-4655 - side only)	Transport/Destination (each) - 4046	\$1,600
Solid non-marking tires	Transport/Destination (each) - 4655	\$2,295
Tech Pro Link connector	Transport/Destination (each) - Alaska and Hawaii (all models)	\$3,500
Tie-down and lifting points	***Please request a quote for freight to Canadian provinces: NL, NS, NT, PE, and YT***	
Platform	Chassis Options	
AC power to platform	AGM maintenance-free batteries ²	\$890.40
Auxiliary platform lowering	Automotive-style horn ¹	\$211.47
Diamond plate platform	Biodegradable hydraulic oil ^{2,3}	\$259.70
Electronic horn	Biodegradable hydraulic oil(for GS-3232, GS-3246) ^{2,3}	\$326.48
Folding guardrails	Drive cutout while charging	No charge
Lanyard attachment points	Power inverter, 800W, 24V DC, 120V AC, 60 Hz ¹	\$1,550.78
	Xtra Height (XH) Full Height Outdoor (GS-1932)	\$638.12
Platform control guard	Certification Options	
Platform load sense system	EE Certification ^{2,3}	\$756.84
Proportional lift	Lift Tools™ Spill Guard (E-drive only)	\$352.45
Slide out extension deck	Platform Options	
SmartLink™ dual zone control system	Air line to platform: 3/8 in. inner diameter	\$756.84

¹ Not available with EE certification

² Not available on GS-4046

³ Consult factory for lead time and availability

⁴ Standard on GS-3232, GS-2046, GS-2646, GS-3246, GS-4046, GS-4655